

Kenworth R&D Center Y993  
485 Houser WY N

Renton, Washington United States 98057  
Phone: (706) 866-0596  
Fax:  
Email:

## Vehicle Summary

Unit		Chassis	
Model:	T680 Series Conventional	Fr Axle Load (lbs):	13200
Type:	FULL TRUCK	Rr Axle Load (lbs)	22700
Description:	T680 FLATBED 3-29-16	G.C.W. (lbs):	35900
Application		Road Conditions:	
Intended Serv.:	Local pickup & delivery.	Class A (Highway)	80
Commodity:	Vehicles which haul	Class B (Hwy/Mtn)	20
	General freight	Class C (Off-Hwy)	00
		Class D (Off-Road)	00
Body		Maximum Grade:	6
Type:	Other	Wheelbase (in):	234
Length (ft):	13.0	Overhang (in):	96
Height (ft):	13.5	Fr Axle to BOC (in):	74
Max Laden Weight (lbs):	5000	Cab to Axle (in):	160
		Cab to EOF (in):	256
Trailer		Overall Comb. Length (in):	380
No. of Trailer Axles:	0		
Type:			
Length (ft):	0.0		
Height (ft):	0.0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions		Special Req.	
Length (ft):	65	U.S. Domestic Registry, 50-State	
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_ Date: \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**



Ask your dealer for a quote today, or visit our website @ [www.paccarfinancial.com](http://www.paccarfinancial.com).

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Kenworth R&D Center Y993  
485 Houser WY N

Renton, Washington United States 98057  
Phone: (706) 866-0596  
Fax:  
Email:

Data	Code	Description	\$ List	Weight
<b>Model</b>				
0000610	O	<b>T680 Series Conventional</b> Primarily for On-highway tractor applications, it features superior aerodynamics, excellent forward lighting and advanced ergonomics. Elastomer bushed front spring pins & heavy-duty shock absorber brackets. 16mm fasteners from rear cab support to end-of-frame, except tractor taper crossmember. Three vinyl inside sunvisors for LH, RH, and center. Under-dash center console with (2) cup holders, (2) 12V outlets & a storage compartment. Glove box door with locking latch.		14,999
0070043	O	<b>T680</b>		0
0080055	O	<b>CARB Idle Emissions Reduction Feature.</b> Cummins engines.		0
0080074	O	<b>CARB Idle Emissions Reduction Feature</b> Label On Hood – Rearward Location		0
0090076	O	<b>76 IN High-Roof or Mid-Roof Sleeper</b> With Rear Axle Capacity Less Than 59K		0
0091090	O	<b>General freight</b> N0099 NON COMMERCIAL N0100 RECREATIONAL APPLICATION		0
0093005	O	<b>Local pickup &amp; delivery. Vehicles which haul</b> freight, typically operating within a 100-mile radius, on public streets & highways, & other paved surfaces, including limited Class C roads. Includes package & freight delivery, as well as fuel oil or petroleum distribution, etc. Road usage: minimum 3% Class B, do not code for Class D. N0095 THIS IS NOT A COMMERCIAL N0096 APPLICATION. THIS IS A N0097 RECREATIONAL APPLICATION		0
0095160	O	<b>Other</b> N0091 FLAT BED		0
0098025	O	<b>U.S. Domestic Registry, 50-State</b>		0

#### Engine & Equipment

0123700	O	<b>ISX15 500 2013 500@1800 463@2000 1650@1200</b> w/Inte Brake, Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. Linehaul Family 2 N09200 N205 120..Standard Maximum Speed Limit [LSL] N09220 N207 0....Expiration Distance N09240 P13 120..Hard Maximum Speed Limit N09260 P14 91...Maximum Accelerator Pedal Vehicle Speed		275
---------	---	--	--	-----

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
		N09280 P16 0....Accelerator Lower Droop		
		N09300 P19 91...Maximum Cruise Speed		
		N09320 P38 0....Cruise Control Lower Droop		
		N09360 N203 474..Reserve Speed Function Reset Distance		
		N09380 N202 0....Maximum Cycle Distance		
		N09400 N206 10...Maximum Active Distance		
		N09420 N201 0....Reserve Speed Limit Offset		
		N09440 P11 Yes..Engine Protection Shutdown		
		N09460 P06 No...Gear Down Protection		
		N09480 P26 1400.Max PTO Speed		
		N09500 P02 Yes..Cruise Control Auto Resume		
		N09520 P04 Yes..Auto Engine Brake in Cruise		
		N09540 N209 0....Expiration Distance		
		N09560 P520 Yes..Enable Idle Shutdown Park Brake Set		
		N09580 P32 5....Timer Setting		
		N09600 P233 Yes..Enable Impending Shutdown Warning		
		N09620 P234 60...Timer For Impending Shutdown Warning		
		N09640 P516 35...Engine Load Threshold		
		N09680 P33 No...Idle Shutdown Manual Override		
		N09720 P230 Yes..Enable Hot Ambient Automatic Override		
		N09740 P46 40...Low Ambient Temperature Threshold		
		N09760 P56 60...Intermediate Ambient Temperature Threshold		
		N09780 P47 80...High Ambient Temperature Threshold		
1000157	O	<b>Prospector Version 37.1</b> Replaces 37.0		0
1000287	O	<b>Enable MX Retarder Downhill Speed Limiter</b> Selecting this code will program the engine to utilize the Downhill Speed Limiter functionality. The Downhill Speed Limiter functionality will control the vehicle to a customer-programmed maximum speed when the engine brake switch is in the ON position, whether or not cruise control is active. 2013+		0
1000684	O	<b>Effective VSL Setting NA</b>		0
1000858	O	<b>Engine Idle Shutdown Timer Disabled</b>		0
1000859	O	<b>Enable EIST Ambient Temp Override</b>		0
1000891	O	<b>Eff EIST NA Expiration Miles</b> Use only with MX and Cummins engines		0
1002070	O	<b>Air compressor: Cummins 37.4 CFM, ISM &amp; ISX.</b> for C500 and T800 Twin Steer use 1002075		15
1051200	S	<b>Air Cleaner: composite firewall mounted PACCAR or</b> Cummins engines		0
1105220	O	<b>Fan Hub: Horton 2-Speed for ISX15</b>		0
1123555	S	<b>Cooling module: 1330 square inches.</b> Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant.		0
1160205	O	<b>Bug screen: Front of grille on C500 ,T800, T880,</b> and W900. Behind grille on T660, T680, and T300 (Medium Duty).		2

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
1160728	O	<b>Lower radiator drain valve Okay for use w/2010+</b> engine cooling modules, other than 1780 square inches.		0
1247185	S	<b>RH under fairing SCR w/ RH horizontal tailpipe</b> below rail		0
1324492	O	<b>DAVCO 483 F/FLTR/H2O SEP, W/12V AND 120V</b> COOLANT HTD FLTR BASE W/ WIF SENSOR		0
1500029	O	<b>Kenworth Fuel Cooler</b> Required for Cummins engines with a single fuel tank. Required for PACCAR MX-13 engine with a single fuel tank and stationary use: High RPM, low vehicle speed, sustained for longer than 1 hour. Optional for all other applications.		6
1504005	O	<b>Immersion block heater 120V 1500W w/plug under</b> door on C500, T660, T800 & W900.		2
1506055	O	<b>Engine oil pan heater 120V 300W w/plug under</b> door on C500, T660, T800 & W900.		2
1507008	O	<b>Block heater &amp; oil pan heater wired to separate</b> plugs.		0
1509035	O	<b>Coolant hoses &amp; 2 shut-off valves for C/I APU</b> coolant hoses routed to 3 feet back-of-sleeper. N1500 USE 8190005. C/I CARRIER N1501 COMFORT PRO INSTALLED N1502 RH BOS.		0
1816260	S	<b>Alternator: PACCAR 160 amp, brush type</b>		0
1825006	O	<b>Batt: 4 Odyssey GP 31 AGM threaded post (1150)</b> 4600 CCA		126
1836100	S	<b>Starter: PACCAR 12 volt electrical system. W/</b> centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.		0
1840006	O	<b>Battery disconnect switches 2, mounted in cab</b> Requires battery box LH under.		2
1840065	S	<b>12V low voltage disconnect for starter battery</b> protection.		0
1900996	O	<b>Jump start terminals under hood.</b>		12
1903034	O	<b>Enable Driver Shift Aid</b>		0
<b>Transmission &amp; Clutch</b>				
2038250	O	<b>Forward Creep Mode Enabled</b>		0
2038251	O	<b>Reverse Creep Mode Enabled</b>		0
2050001	O	<b>01/01/15 list price adjust - Eaton FR/FRO/FRM</b> transmissions		0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
2058460	O	<b>Transmission: Eaton FO16E313A-MHP UltraShift Plus</b> 13-speed w/Hill Start Aid feature. Standard with synthetic lubricant. This product should be used for long haul over the road applications. C500, T660, T800 & W900 models utilize a cobrahead shift lever. *Torque Limit: 1650 pound-feet.		295
2250385	O	<b>Clutch:UltraShift Plus OR Fuller Advantage Series</b> Automated transmissions.		0
2406453	O	<b>Driveline: 2 Dana SPL250XL 1 centerbearing</b> requires 3500057 interaxle driveline. Low maintenance offering from Spicer. On-highway 350K mi first service interval, 100K mi subsequent service interval on U-joint, splines lubed for life for life, quick disconnect end caps.		95
2410705	O	<b>AutoShift/UltraShift cobrahead control integrated</b> into dash.		0
2450114	O	<b>ADD TRANS FILTER: EATON ULTRASHIFT PLUS</b> *Optional below 2050 lb-ft torque. Filter is installed on the transmission by Eaton.		0
2460042	O	<b>14 in. Eaton Fuller high capacity oil to water</b> cooler standard for transmission 1550-2250 lb-ft, 18-speed AutoShift.		0
2493009	O	<b>Aluminum clutch housing</b>		0
<b>Front Axle &amp; Equipment</b>				
2502326	O	<b>Dana Spicer E-1322W Front Axle rated 13.2K</b> 3-1/2in. drop, wide track for better turning radius.		35
2607001	S	<b>Front Brakes: 14.6K Bendix air disc brakes lube</b> free.		0
2690024	S	<b>Splined rotor for front air disc brakes for use</b> with aluminum hubs.		0
2701300	S	<b>Front Hub: aluminum hub pilot 13,200 lbs.</b> 10-Bolt, 11-1/4 in. bolt circle .		0
2741970	S	<b>ConMet PreSet Plus Hub package; front axle.</b>		0
2750001	S	<b>Hubcap: front vented.</b>		0
2769000	S	<b>Slack Adjusters included w/ front axle or brake.</b>		0
2864012	O	<b>Front Springs: Taperleaf 13.2K w/ shock absorbers</b> w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins. Not available on W900L.		9
2895221	S	<b>Single power steering gear: 13.2K Sheppard HD94.</b>		0
2899336	O	<b>Power Steering Cooler: Radiator mounted air to</b> oil 2007+ engines only. 2899362 is optional w/ 2006 or 2007 engines.		11
2900615	O	<b>Threaded bushings for taperleaf springs</b> 12K - 14.6K replacing rubber: T6/T8 & W9B only. W9L gets as standard: code not required. Not available with W9S.		0
2900903	O	<b>Front air disc brake dustshield includes pad</b> air disc brakes only.		1

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
<b>Rear Axle &amp; Equipment</b>				
3041190	O	<b>Single Dana Spicer S23-190 single reduction rear</b> axle. Single rear axle rated at 23K. N3040 add 3510000 tapered axle shaft N3041 holes		-1,889
3200307	O	<b>Rear Axle Ratio - 3.07.</b>		0
3302001	O	<b>Single rear Bendix air disc brakes for single</b> rear axles to 23K capacity.		20
3392204	O	<b>Splined rotor for single rear air disc brakes for</b> use with aluminum hubs.		-104
3401010	O	<b>Single Rear Hubs: Aluminum hub pilot 23K;</b> 11-1/4 in. bolt circle.		0
3441971	O	<b>ConMet PreSet Plus Hub package; single rear axle.</b>		0
3465900	O	<b>Rear slack adjusters included w/ axle or air</b> disc brakes.		0
3485004	O	<b>Spring brakes included w/ single rear air disc</b> brakes.		0
3490901	O	<b>Rear air disc brake dustshields for single axle;</b> includes pads and rotor shields.		6
3495228	O	<b>Bendix 4S/4M anti-lock brake system w/ air</b> traction control (ATC).		2
3531001	O	<b>Wheel Differential Lock for Dana Spicer Axles</b> S21-170, S21-190, S23-170, S23-190, S26-190 & S30-190; adds D to the end of the axle part number.		0
3634030	U	<b>Rear suspension: single Neway ADZ123 23</b> K.		-436
3836500	O	<b>Heavy-duty gussets for forward suspension</b> crossmember on Airglide 400/460, Chalmers, or Hendrickson beam suspensions. This replaces the standard gussets. N3830 add 3839002 overinflation valv		12
<b>Tires &amp; Wheels</b>				
4077480	O	<b>Front tires: Bridgestone R283ECOPIA 295/75R22.5</b> 16PR. 40.3 in. diameter, all position 18.8 in. SLR. Smartway certified.		2
4277408	O	<b>Rear tires: Bridgestone M760 Ecopia 295/75R22.5</b> 14PR 40.7in. diameter. 27 tread depth. 19.0in. SLR. EPA SmartWay verified.		36
4900004	O	<b>Rear Tire Quantity: 4</b>		0
5045186	O	<b>Front wheel: Kenworth 7-spoke 88768</b> 22.5x8.25 aluminum with Lvl One [TM] finish, hub pilot mount. 7300lb. maximum rating. Level 1 finish. Air disc brake compatible.		-42
5245186	O	<b>Rear wheel: Kenworth 7-spoke 88768</b> 22.5x8.25 aluminum with Lvl One [TM] finish, hub pilot mount. 7300 lb. maximum rating. Air disc brake compatible. Code is priced per pair of wheels. Level 1 finish.		-84
5850040	O	<b>Wheelguards: all axles.</b>		2

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
5859011	O	<b>Single rear axle wheels: 2 wheels Dura-Bright</b> Buffed. Dura-Bright outboard surface of outer dual or single aluminum wheels.		0
5859013	O	<b>SING RR: DURA-BRIGHT INBD SURF OF INNER</b> WHL(2)-2DB*REQ WHLGRDS*USE W/5859011		0
5859014	O	<b>Single front axle wheels Dura-Bright Buffed both</b> outboard & inboard surfaces of aluminum wheels.		0
5900004	O	<b>Rear Wheel/Rim Quantity: 4</b>		0
<b>Frame &amp; Equipment</b>				
6056600	O	<b>Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel 337in.</b> to 416 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.		525
6308731	O	<b>Bumper: Steel Aerodynamic, Chrome.</b> Requires a bumper setting code.		76
6319504	S	<b>50.4 in. Bumper setting. Requires a bumper code.</b>		0
6321005	O	<b>Removable Front Tow Hooks: 2.</b>		15
6390091	O	<b>Frame layout picture to dealer prior to build</b> date. Information only, no changes. This provides basic frame layout illustration in a PDF file. Adobe Reader or other software capable of viewing PDF files is required on your computer. A copy of the frame layout can be obtained once the engineering work has been completed. This drawing will help the body builder define clearance requirements for the chassis.		0
6390103	S	<b>Front mudflaps.</b>		0
6391201	O	<b>Custom Frame Layout: one chassis</b>		0
6405045	S	<b>T6 Battery box module: Short length, aluminum</b> parallel, w/ polymer cover. Located LH under cab behind the chassis fairing. For use only w/ 2010 SCR style exhaust.		0
6409901	O	<b>Battery box location: LH Side.</b>		0
6419020	O	<b>Forward fairing removable access door, for LH side.</b>		2
6419505	O	<b>Chassis Fairings 76 in. Sleeper: Partial fairings</b> on both sides. Without integral frame access.		65
6451037	O	<b>Cab side skirt: Supports on RH side.</b>		55
6490600	U	<b>CODE # 6490602 FRAME SPACE; C/IAPU RH S</b> IDE INBOARD OF PARTIAL FAIRING;76"SLPR		0

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
6497106	O	<b>First - RH outside and RH below rail only.</b> Clear frame space area. Does not include fasteners or piping. Requires a supplemental length and location code. Sales tool graphics do not depict interference between requested location and other frame-mounted components. The actual chassis layout will be determined at time of engineering.		0
6497113	O	<b>Second - LH outside and LH below rail only.</b> Clear frame space area. Does not include BOC crossmember, fasteners or piping. Requires a supplemental length and location code. Sales tool graphics do not depict interference between requested location and other frame-mounted components. The actual chassis layout will be determined at time of engineering.		0
6497360	O	<b>First - 60 in. clear frame space length.</b> The impact to other frame-mounted components will be determined at time of engineering.		0
6497560	O	<b>Second - 60 in. clear frame space length.</b> The impact to other frame-mounted components will be determined at time of engineering.		0
6498000	O	<b>First clear space starting 0 in. behind cab</b> measured from rear cab face, regardless of sleeper presence		0
6499000	O	<b>Second clear space starting 0 in. behind cab</b> measured from rear cab face, regardless of sleeper presence		0
6679864	O	<b>Final end-of-frame cut-off dimension will be</b> modified to greater than or equal to 75 in.		0
6679915	O	<b>Customer-installed bulkhead and/or headache</b> rack.		0
6721102	S	<b>Rear mudflap arms: Betts B-25 standard-duty,</b> straight. Includes B1732 mounting brackets as standard.		0
6722000	S	<b>Rear mudflap shields: White plastic antisail w/</b> Kenworth logo.		0
6741011	O	<b>Square end-of-frame w/ crossmember; non-towing.</b>		30
<b>Fuel Tanks &amp; Equip</b>				
7214120	O	<b>Fuel Tank: 120 US gallon 24.5in. aluminum BOC</b> replace. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck.		6
7216090	O	<b>Fuel Tank: 90 US gallon 24.5in. aluminum BOC add.</b> Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck. Multiple tank installations include a fuel equalization system w/ dual draw and return lines with a splitter valve located within 6 inches behind the cab. Single draw and return is an option in some cases.		108
7722024	O	<b>Aerodynamic round DEF tank. 26.7 gallons</b> of useable volume. The tank will be located just rearward of the under cab component on the LH side. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.		39

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
7889014	O	<b>Fuel fill under sleeper, LH fairing. Use with</b> 76 in. sleeper only. LH Under sleeper fill will be able to accommodate LH fuel tanks up to 90 gallons (short hood or medium hood) with LH DEF, or fuel tanks up to 90 gallons (short hood or medium hood) with RH DEF before the tank grows rearward.		2
7889016	O	<b>Fuel fill under sleeper, RH fairing. Use with</b> 76 in. sleeper only. RH Under sleeper fill will be able to accommodate RH fuel tanks up to 110 gallons (short hood), 120 gallons (medium hood) with LH DEF, or fuel tanks up to 90 gallons (short hood or medium hood) with RH DEF before the tank grows rearward.		2
7889021	O	<b>Fuel tank locking cap(s). Not available w/</b> hydraulic tank. Tank lock does not match ignition/cab/sleeper locks.		0
7889203	O	<b>Standard DEF to fuel fill ratio: 2:1 or greater.</b>		0
7889604	O	<b>DEF tank location is on the LH.</b>		0
7930120	O	<b>Location: 120 gal fuel tank RH behind cab</b>		0
7940090	O	<b>Location: 90 gal fuel tank LH behind cab</b>		0
<b>Cab &amp; Equipment</b>				
8025301	S	<b>Cab: Stamped aluminum cab with panoramic curved</b> glass windshield. Standard with stamped aluminum doors, heavy duty in-swinging hinges, and triple sealed doors. Manufactured using self-piercing rivets and structural adhesive. Includes LED exterior marker lights and turn signals.		0
8071676	O	<b>Sleeper: 76in Integral High-Roof Aerodyne</b> With LH and RH Windows, Locking Tool Doors		1,198
8080942	O	<b>Sleeper door, LH/RH w/ sliding window.</b>		19
8090603	O	<b>Hood: T680 125 inch BBC with side of hood air</b> intake.		10
8108002	O	<b>Fine particulate filter for cabin air HVAC</b> system. To provide extra filtration in high dust applications. Cabin airflow is reduced with this additional filter. *Cannot be used with code 8108003.		0
8178213	O	<b>Cab/Sleeper HVAC system.</b> Cab HVAC includes defrost, A/C, and 48,000 BTU/hr heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter for cab system & recirculation filters for cab/sleeper cabin air are standard. Sleeper HVAC includes A/C and 40,000 BTU/hr heater. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without the need for additional insulation.		0
8201043	O	<b>Kenworth Smartwheel: 18 in. Leather Wrapped With</b> Integrated Radio and Cruise Controls.		2
8201200	S	<b>Adjustable telescoping tilt steering column.</b>		0
8203060	O	<b>5 sets of keys. Replaces standard 2 sets of keys.</b>		0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
8203184	O	<b>Switch &amp; Wiring: For Customer-Installed Cab Panel</b> Lights.		1
8205038	O	<b>Controls on dash for pintle hook.</b> Includes piping.		2
8205082	O	<b>Controls on dash for trailer air suspension.</b> Includes piping & indicator light. * Dash controls for trailer functions require that you add trailer connections to the order. * This trailer air suspension valve provides an air control. There is an option for trailer hotwire that provides an electric control wired to a dash switch. * Optional speed interlock available on T660/T680 models.		0
8205154	O	<b>Two (2) spare accessory electric-over-air switch</b> with non-latching air solenoid. Non-Latching means the output air pressure will turn off when the ignition is off regardless of switch position. Do not use this switch for options that will allow the vehicle to move with ignition off, such as: trailer suspension dump or trailer lift axles. Mounted on dash for customer-installed option. Air pressure is removed when ignition is off. Not intended for Trailer Lift Axle controls		0
8205160	O	<b>Dash SW:Bendix Work Brake Electric Over Air SW To</b> Apply All Service Brakes		5
8208549	O	<b>Seven-way plug: Wired to dash switch. For trailer</b> power. Includes indicator light. Center pin of standard 7-way connector (J560) will be wired to a switch for trailer hotline. Switch is wired to a battery circuit & has an integral indicator lamp.		0
8208582	O	<b>ISO 3731 Spare circuit switch 1 ID: For trailer</b> floodlight. Includes indicator light. Provides a switch connected to one spare circuit in the ISO 3731 connector labeled for trailer floodlights w/an integral indicator light.		0
8208598	O	<b>ISO 3731 Spare circuit switch 2 ID: For trailer</b> hotline. Includes indicator light & guard.		0
8208609	U	<b>SW:ONE SPARE ACCESSORY ELEC-OVER-AIR SW</b> W LATCHING AIR SOLENOID		0
8209999	O	<b>Spare Power Wiring For Customer Installed Devices</b> Behind Dash Cluster. Includes 2 batt, 2 ign, 1 acc, 1 LVD at 20A each.		2
8220112	O	<b>Virtual Gauge: NavPlus HD Air Filter Restriction</b> Gauge.		0
8221144	O	<b>Gauge: Air suspension pressure gauge.</b>		0
8221150	U	<b>VIRTUAL GAUGE: TRAILER RESERVOIR AIRE P</b> RESSURE		0
8221151	U	<b>GAU: VIRTUAL GAUGE - TRAILER AIR APPLIC</b> ATION		0
8221154	U	<b>GAU:VIRTUAL GAUGE - 2 ADDITIONAL AIR PR</b> ESSURE GAUGES		0
8222712	O	<b>Gauge: Fuel filter restriction gauge.</b>		0
8222722	O	<b>Gauge: Manifold Pressure Gauge.</b> The NavPlus HD unit includes a virtual manifold pressure gauge.		0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
8224401	O	<b>Gauge: Ammeter gauge in addition to voltmeter.</b> W/integral warning light.		0
8225626	O	<b>Gauge: Axle oil temperature gauge. Single drive</b> axle or forward rear axle w/integral warning light.		0
8226667	O	<b>Gauge: Oil Temperature Gauge Transmission.</b> The NavPlus HD unit includes a virtual transmission oil temperature gauge.		0
8227703	U	<b>GAU: VIRTUAL GAUGE: - FUEL GAUGE FOR SE</b> COND FUEL TANK		0
8282007	S	<b>Kenworth Driver Performance Center:5in Full Color</b> high resolution Thin Film Transistor (TFT) active matrix display with advanced driver information including fuel economy performance, outside air temp, clock, odometer and trip, engine hour meter, ignition timer, engine RPM, general truck information, diagnostics, and gear display. All Highline functionality is accessed via the Kenworth MCS providing intuitive control at the driver's fingertips. Also includes Dark Cabin functionality. When activated, the only interior light that will function when a door is opened is the door courtesy lamp.		0
8282013	S	<b>Kenworth instrumentation and control package with</b> 9 standard easy-read gauges: includes speedometer, tachometer, fuel gauge, engine coolant temp, engine oil pressure, voltmeter, dual air pressure, air application pressure and DEF gauge. All accessory controls utilize electronically activated solenoids that include advanced vehicle protection interlocks.		0
8300008	S	<b>Interior color: Slate Gray</b>		0
8330178	O	<b>Interior Package: Diamond VIT Cab 76in Sleeper</b> Includes diamond design trim with premium wood grain accent trim and anodized aluminum accents throughout. Standard with Kenworth NavPlus HD on 2010 and later engines. Large overdoor storage bins with doors, overhead storage cubbies, full size glove box, two center console cupholders, and large door pad map pocket. Standard LH and RH power windows, electric door locks, interior LED lighting, nighttime friendly red ambient lighting for dash and cab footwell, and door mounted courtesy light. Includes single 42in. liftable premium pocket coil lower bunk. Also includes four standard 12V power outlets throughout the cab and sleeper. Driver sunvisor includes vanity mirror and strap, passenger sunvisor includes strap.		0
8390634	S	<b>Rubber floormat</b>		0
8410354	O	<b>DR Seat: GT703 HB with Two-tone Leather material,</b> integral HEAT and air-COOLING. The GT703 is standard with a single air bag, scissor linkage seat suspension that incorporates seat height memory, auto-leveling valves with exit air dump, and adjustable damper. It includes adjustable bolsters, an articulating headrest, a dual chamber lumbar support, 10in Fore/Aft adjustment, 5in Up/Down adjustment with protection zones, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. Seat storage package is standard with the GT703. Includes 3-point matching seat belts. DR seat standard w/ dual armrests.		10

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
8460354	O	<b>RD Seat: GT703 HB with Two-tone Leather material,</b> RD Seat: GT703 HB with Two-tone Leather material, integral HEAT and air-COOLING. The GT703 is standard with a single air bag, scissor linkage seat suspension that incorporates seat height memory, auto-leveling valves with exit air dump, and adjustable damper. It includes adjustable bolsters, an articulating headrest, a dual chamber lumbar support, 10in Fore/Aft adjustment, 5in Up/Down adjustment with protection zones, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. Seat storage package is standard with the GT703. Includes 3-point matching seat belts. RD seat standard w/ LH armrest.		44
8490187	S	<b>Seat color: Slate Gray with Gray stitching.</b>		0
8497005	O	<b>Air line fitting: At driver seat.</b> Customer-installed air chuck.		4
8497465	O	<b>Seat Swivel for Kenworth GT Series RD Seat</b>		50
8498453	O	<b>Dual KW driver seat armrests: Stowable inboard &amp;</b> folding outboard.		2
8498553	U	<b>Dual rider seat armrests: Stowable inboard &amp;</b>		0
8505070	O	<b>Drawer-style refrigerator with integral freezer</b> compartment and LED lighting. Mounted at mid-height on driver's side of 76in Sleeper.		40
8505101	O	<b>TV Installation Package for 76in. SLPR: Wall</b> Mounted, Articulated Arm, Passenger Side Above Table and Between Upper and Lower Storage Modules. 22in. Flat Screen Maximum.		4
8520018	O	<b>Liftable Lower Bunk For 76 in. SLPR:</b> 42 in. x 80 in. Pocket Coil Mattress		0
8520984	O	<b>Stowable Upper Bunk For High Roof 76in. SLPR:</b> 30 X 78 Foam Mattress. Includes Upper Bunk LED Reading Lamp and Tent Style Bunk Restraints.		66
8521000	O	<b>EVA foam pad over mattress tray: For insulation</b> 9/16 in. thick.		2
8570026	O	<b>Driver Side Upper Storage Unit: Wardrobe Closet</b> with Door and Shelf for 76in Aerodyne Sleeper.		56
8570031	O	<b>Driver Side Lower Storage Compartment</b> with open space for refrigerator. Opening is 15.5 inches wide, 20.5 inches high, and 19.3 inches deep. Use with 8505070 or 8505076.		40
8570035	O	<b>RD Side Upper Storage Unit</b> Open microwave compartment with tiedown. Standard 12 volt outlet and open storage compartment on top. Dimensions for the microwave compartment are 19.5 inches wide by 12.5 inches high by 15 inches deep. 120V outlet available in the storage unit with the addition of sales code 8700912 or 8700907.		31
8570038	O	<b>Rider Side Lower Storage Unit: Rotating table,</b> DVD tray, and two lower drawers. Includes ambient lighting for table and sleeper footwell.		74

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
8601880	O	<b>CB Radio: Cobra 29. Includes weatherband w/header</b> mounted quick release. Includes transceiver & separate speaker remote-mounted in headliner & dual CB antennas. Includes sound tracker & illuminated panel.		11
8698996	O	<b>Premium Audio System - Sleeper: Amplified high</b> performance door, B-Pillar, and back wall speakers with A-Pillar tweeters and 10 inch subwoofer. The amplifier is rated to 320 watts and contains a digital signal processor (DSP) that is specifically tuned to the interior.		29
8700168	S	<b>Non-self cancelling turn signal: W/column-mounted</b> headlight dimmer switch & intermittent wiper control.		0
8700188	O	<b>Remote Keyless Entry</b>		0
8700406	O	<b>Stainless steel permit panel on cab, driver side</b> only		0
8700707	O	<b>Cummins Road Relay 5.</b>		2
8700847	U	<b>J1939 Harness: Routed Behind Glove Box.</b>		0
8700907	O	<b>76in. Sleeper Power Option Package 2: 1800W</b> Inverter With 120V Low Voltage Disconnect For Starter Battery Protection, 4 120V Sleeper Outlets, Shore Power Connection and Battery Charger.		22
8800402	S	<b>Dual Cab Interior Grabhandles: A Pillar Mounted</b> Dash Wrap and B Pillar Mounted Grabhandles		0
8806008	O	<b>Kenworth Aero Package Code</b>		0
8829600	S	<b>Fairing under cab w/ integral steps.</b>		0
8829617	O	<b>Side extenders: 76 inch high-roof sleeper.</b> 5-piece set extends 19 inches from back-of-sleeper and includes 7 inch rubber trailing edge. Extender set includes lower (sleeper), upper (sleeper roof), and top (sleeper roof top) extenders.		28
8832113	S	<b>Kenworth Daylite Door with standard LH/RH</b> electric door locks and LH/RH electric window controls.		0
8841411	S	<b>Single air horn under cab.</b>		0
8850139	S	<b>Look-Down, Pass. Door, Black 11x6</b>		0
8850827	O	<b>Dual Hood Mtd Blind Spt, Chrome 8x6 Htd</b>		4
8865003	U	<b>Aero Mirror: Dual Kenworth Chrome Aero.</b> Motorized		0
8879439	O	<b>Windshield Curtain with Integrated Curtain</b> Track and Storage at B Pillar for 76in Sleepers only. Curtain runs along perimeter of the cab so maintains full use of cab and sleeper interior space. Not available on Daycabs.		2
8890101	S	<b>One-piece bonded-in windshield with curved glass.</b> Standard.		0
8890876	S	<b>Kenworth Cab/Sleeper Air Suspension.</b>		0
8891015	O	<b>Extreme Temperature Insulation: 76 inch Sleeper</b> Additional Cab and Sleeper Side Wall Insulation With Improved Material Properties Over Standard Insulation Package.		1

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
<b>Lights &amp; Instruments</b>				
9010401	O	<b>Headlamps: High Intensity Discharge (Xenon)</b> Projector Module Low Beam, Halogen Complex Reflector High Beam.		0
9027110	O	<b>Marker Lights: Five LED rectangular, flush mount.</b>		0
9030016	S	<b>Turn Signal Lights: Flush mounted LED mounted at</b> top of fender wheel arc		0
9030034	O	<b>Wiring: Customer Installed Turn Signals,</b> Mid Chassis.		0
9030052	S	<b>LED Stop,Turn,Tail:Flange Mounted With Two LED</b> backup lights and with an LED license plate.		0
9058071	O	<b>Switch, Wiring, and Indicator Light for Customer</b> Installed Floodlights. 1st Set. Pigtail Routed Through Pass Thru Grommet. 10ft Jumper Harness Shipped Loose.		1
9058072	O	<b>Switch, Wiring, and Indicator Light for Customer</b> Installed Floodlights. 2nd Set. Pigtail Routed Through Pass Thru Grommet. 10ft Jumper Harness Shipped Loose.		1
9058073	O	<b>Switch, Wiring, and Indicator Light for Customer</b> Installed Floodlights. 3rd Set. Pigtail Routed Through Pass Thru Grommet. 10ft Jumper Harness Shipped Loose.		1
9059901	O	<b>Floodlight Location: Located high - first set</b>		0
9059903	O	<b>Floodlight Location: Located high - second set.</b>		0
9059924	O	<b>Floodlight Location: Located low - third set.</b>		0
9090037	O	<b>Trailer Marker Lights w/ Separate Switch</b>		0
9090039	S	<b>Marker Lights: Interrupter Switch.</b> Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash.		0
9090102	O	<b>Anti-Theft System Installed</b>		0
9090117	O	<b>Marker Lights: Midframe</b> & reflectors mounted standout. Required on tractors where overall length exceeds 30 feet.		22
9090142	O	<b>Wiring Only: For customer-installed backup</b> alarm.		0
9090302	U	<b>Junction Box: Mounted Behind Cab or SI</b> eeper		0
<b>Air Equipment</b>				
9101235	O	<b>Air Dryer: Bendix AD-IS Extended Purge heated.</b> with PuraGuard		4
9108001	S	<b>Moisture ejection valve w/ pull cable drain.</b>		0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Data	Code	Description	\$ List	Weight
9110034	O	<b>Full truck/tractor kit combined: Center frame</b> mounted. 7-way female receptacle and air connection gladhands are mounted BOC on center frame bracket & mounted at end-of-frame in taillamp bracket. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve, tractor protection valve, and spring brake inversion/relay valve are standard.		15
9120010	O	<b>Air and light line length 10 feet</b>		0
9140005	O	<b>Straight air &amp; light lines: for semitrailer</b> application. Air lines detachable one end only; light line detachable both ends. Use w/ code 9110030. Note must code separately for straight air & light line lengths. Requires 12ft straight air & light.		8
9140020	S	<b>Nylon air tubing in frame &amp; cab, excluding hoses</b> subject to excessive heat or flexing.		0
9140101	O	<b>Charging gladhand: Frame bracket &amp; air line to</b> wet tank.		2
9140252	O	<b>Locate air dryer inside LH rail BOC.</b> This code requires the use of a custom frame layout code.		0
9140289	O	<b>Air tanks: mounted inside frame flanges</b> where possible. This code requires the use of a custom frame layout code.		0
9140336	O	<b>Additional 7-way ISO 3731 connector for trailer</b> ABS power. Additional, w/ 15ft coiled light line, for combined full truck & tractor.		13
9140342	O	<b>Two spare circuits through trailer ABS ISO 3731</b> connector, spare circuits wired to two dash switches. Requires sales code 9140321 or 9140322. Spare Switch 1 is wired to Pin 4, Spare Switch 2 is wired to Pin 5		0
9140702	O	<b>Optional Hosetenna Bracket Location 2ft</b> BOC/sleeper. Hosetenna bracket will be located plus or minus six inches from any non-standard location requested		0
9150100	U	<b>AIR TANK: ONE EXTRA 8"X41" OR EQUIVALEN</b> T VOLUME		0
9150170	O	<b>Air tanks: aluminum replacing steel all tanks.</b> *NOT AIR TANKS ON LIFT AXLES		-44
<b>Extended Warranty</b>				
9200021	S	<b>Standard Warranty.</b>		0
<b>Miscellaneous</b>				
9409852	O	<b>GHG Secondary Manufacturer: Does Not Apply</b>		0
9490206	O	<b>Warning triangle reflector kit: Shipped loose.</b> Kit consists of 3 triangles in plastic carrying case. Not floor mounted.		4
9490413	O	<b>One 5 lb. dry chemical type fire extinguisher</b> mounted LH of sleeper toolbox. Class ABC.		11

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.



Data	Code	Description	\$ List	Weight
<b>Paint</b>				
9700000	O	<b>Paint color number.</b> N97020 A - N97200 FRAME N0001 BLACK N97800 CH FAIRINGS		0
9943004	O	<b>Bumper Unpainted</b>		0
9943005	O	<b>Chassis Fairings Painted A Color</b>		0
9943055	O	<b>Sleeper Pearl/Metallic Paint</b>		0
9944821	O	<b>1 - Color Paint - Sleeper</b> Color will be White if no other color is specified.		0
9965510	S	<b>Base coat/clear coat.</b> The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.		0

Total Adjusted Price (W/O Freight & Warranty & Surcharges)

Freight Charge

Options Not Subject to Discount

Surcharges Not subject to Discount

Total Weight

16136

**Prices and Specifications Subject to Change Without Notice.**

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.